

Quick and easy to use

Light weight, reduces operator effort

Accommodates

In basket harness release system, allows rapid change of replacement harnesses

uneven surfaces

Easy basket replacement

**Compact stowed** footprint

Accommodates uneven surfaces

Compact stowed footprint





Crocodile Cable Carrier is part of the Plane Power Aviation product range

## **TECHNICAL FEATURES**

Unique Articulating Pivot Joint integrated at intermediate joints & fixed end – allows carrier arms to move freely in response to un-even surfaces. Removes component stresses and reduces maintenance requirements

## **TECHNICAL DETAILS**

Deployment Lengths:	6m, 12m, 18m, 24m & 30m
Installation Handing	Right hand or Left hand as required
Outputs	400Hz; Single, Double & Quad (28V DC can also be supplied)
Beam Construction	Aluminium Alloy with easy access covers for cable access
Basket Construction	Aluminium Alloy 6082 T6 with removable mesh baskets
Basket Size	<b>Single/Double</b> -1.12m x 0.48m x 1.2m (L x W x H)
	<b>Quad</b> -1.12m x 0.96m x 1.2m (L x W x H)
Basket Cable Length	Single & Double available in 6.5m, 11.5m or 15m. Quad 8.5m
Basket Harness Cable Type	4 x 70mm² and controls
Basket Controls /Indicators	Per output;
	400Hz available LED indicator
	LED illuminated Start/On push button
	Stop pushbuttons
	· ·
	Easy Access Emergency Stop (wired into control circuitry)
Wheel Type	
Wheel Type	(wired into control circuitry)  Wheel body-Polyamide 6 with
Wheel Type	(wired into control circuitry)  Wheel body-Polyamide 6 with two precision ball bearings  Tyre-Wrap-around elastic polyurethane with low rolling
Wheel Type  Wheel Diameter	(wired into control circuitry)  Wheel body-Polyamide 6 with two precision ball bearings  Tyre-Wrap-around elastic polyurethane with low rolling resistance profile

Control Box Sealing	Fixed end & Basket end sealed to IP66
Fixed End Stop Construction	Mild Steel
Finish	Bright Yellow Gloss to BS 08E51, other colours available on request
Cable Spec	Power cable 7 x 35mm² Twisted Single Core Cable (1 off central neutral, 3 x 2 off balanced phase conductors) – 450 Volt Multi Stranded cable to BS 638
	Control cable 1.0mm² 3GKW
	Earth Cable, bond and PE 35mm – Green/yellow stripe
Basket Brake System	2 x Foot operated stamp jack
Stowed Footprint	Single/Double;
	6m – 3.4m (W) x 1.2m (D)
	12m – 3.4m (W) x 1.6m (D)
	18m – 3.4m (W) x 2.0m (D)
	24m – 3.4m (W) x 2.4m (D)
	30m – 3.4m (W) x 2.8m (D)
	Quad
	6m – 3.4m (W) x 1.7m (D)
	12m – 3.4m (W) x 2.1m (D)
	18m – 3.4m (W) x 2.5m (D)
	24m – 3.4m (W) x 3.1m (D)
	30m – 3.4m (W) x 3.5m (D)
Applicable Certification	CE Marking, ISO 9001:2015, ISO, IEC17050-1, BS EN1915-1,2,3,4,



Plane Crocodile Cable Carrier is part of the Plane Power Aviation product range Plane Power Aviation product range

