

DEKAL LOAD BANKS®

DEKAL LOAD BANKS * DEKAL AGREGATI LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA - EUROPE



DEKAL LOAD BANKS USA LLC
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 - USA




Tel.: +386 2 320 325 0 * Fax: +386 2 320 325 2
Email: info@dekalloadbanks.com
Web: www.dekalloadbanks.com

Tel.: +1.800.323.9172
Cell: +1.954.516.4245
Email: info@dekalloadbanks-us.com
Web: www.dekalloadbanks-us.com

PORTABLE POWER ANALYZER FOR AC & DC POWR MEASURING BETWEEN GPU AND AIRCRAFT - WiFi & USB CONNECTIVITY



TECHNICAL SPECIFICATION	ANA-028	ANA-428	ANA-400	ANA-440
AC VOLTAGE [V]	/	115 /200 V AC ± 20 %	115 /200 V AC ± 20 %	115 /200 V AC ± 20 %
AC LOAD [A]	/	0 - 180 kW ± 10 %	0 - 180 kW ± 10 %	0 - 180 kW ± 10 %
FREQUENCY [Hz]	/	400 Hz ± 20 %	400 Hz ± 20 %	400 Hz ± 20 %
DC VOLTAGE [V]	28.5 V DC ± 20 %	28.5 V DC ± 20 %	/	/
DC LOAD [A]	0 - 2500 A ± 10 %	0 - 2500 A ± 10 %	/	/
3 LINE HIGH BRIGHTNESS RED LED DISPLAY CLASS: ±0.5% S ACC. IEC 62053-22 2003	/	V, A, Hz, kW, kVA, Unbal. % load, cos φ	V, A, Hz, kW, kVA, Unbal. % load, cos φ	V, A, Hz, kW, kVA, Unbal % load, cos φ
3 LINE HIGH BRIGHTNESS RED LED DISPL. CLASS: ±0,5 % FS±2C	V, A, kW	V, A, kW	/	/
PLUG TEST PINS FOR EXTERNAL INSTRUMENT DEVICE	1 x +, -, E, F (DC)	1 x A, B, C, N, E, F (AC) 1 x +, -, E, F (DC)	1 x A, B, C, N, E, F (AC)	2 x A, B, C, N, E, F (AC)
I/O between GPU and AIRCRAFT	1 x 28 V DC	1 x 28 V DC and 1 x 400 Hz	1x 400 Hz	1 x 400 Hz and 1 x 400 Hz
INDICATIONS	1 x POWER, CONTROL INDICATION	1 x INTERLOCK, PHASE INDICATION, PHASE ROTATION 1x POWER, CONTROL INDICATION	1 x INTERLOCK, PHASE INDICATION, PHASE ROTATION	2 x INTERLOCK, PHASE INDICATION, PHASE ROTATION
CONNECTION TO DEVICE WITH EMBEDDED & INCLUDED FREE DEKAL LICENSED SOFTWARE	WiFi & USB			
NORMS				
TESTING PROCEDURE ACCORDING	ISO 6858, DSF 400, ARP 5015			
DEVICE CLASSIFICATION	CE marking, DIN, VDE, IEC			
DIMENSIONS & WEIGHT				
ANALYZER SIZE [L x W x H] mm / Kg ANALYZER SIZE [L x W x H] In / Lbs	520 x 250 x 230 / 18 20.5 x 9.8 x 9 / 40	520 x 250 x 230 / 18 20.5 x 9.8 x 9 / 40	520 x 250 x 230 / 18 20.5 x 9.8 x 9 / 40	520 x 250 x 230 / 18 20.5 x 9.8 x 9 / 40
TRANSPORT CASING [L x W x H] mm / Kg TRANSPORT CASING [L x W x H] In / Lbs	840 x 380 x 580 / 22 33 x 15 x 23 / 48	840 x 380 x 580 / 22 33 x 15 x 23 / 48	840 x 380 x 580 / 22 33 x 15 x 23 / 48	840 x 380 x 580 / 22 33 x 15 x 23 / 48
ANALYZER PAINTING / TRANSPORT CASING	POWDER COATING FINE STRUCTURE 71319 IGP, SWISS QUALITY / HIGH GRADE ALUMINUM			
Including transport carrying case per unit / All specifications are subject to change without further notice				



DEKAL LOAD BANKS®

DEKAL LOAD BANKS * DEKAL AGREGATI LLC
UL. LUDVIKA PLAMBERGERJA 25
SI-2204 MIKLAVZ NA DR. POLJU
SLOVENIA - EUROPE



DEKAL LOAD BANKS USA LLC
2000 TECHNOLOGY DRIVE
PITTSBURGH, PA 15219 - USA



Tel.: +386 2 320 325 0 * Fax: +386 2 320 325 2
Email: info@dekalloadbanks.com
Web: www.dekalloadbanks.com

Tel.: +1.800.323.9172
Cell: +1.954.516.4245
Email: info@dekalloadbanks-us.com
Web: www.dekalloadbanks-us.com

ADVANTAGES OF DEKAL ANALYZER

- **Simple operation** suitable for non-trained operators
- **28.5 V DC power measuring**, connected between GPU and Aircraft
- Suitable for **workshop and/or airside operation**
- **115 - 200V / 400 Hz V AC power measuring**, connected between GPU and Aircraft
- **Time duration and kW consumption** indication option for **energy charge**
- **Transport casing** with pull up handle as standard **for each analyzer**
- **Customized model configuration**; DC, AC, DC/AC, AC/AC, analyzer models
- **Free DEKAL licensed software application & proper drivers included**
- **Accurate measurements possible to export and printout in PDF or excel files**
- **High component quality control** by manufacturer
- **High reliability** - effective standardization process
- Isolated jack sockets - **unique user friendly safety feature** for external voltage test
- Spare parts availability and **accurate on-time deliveries**
- Aluminum housing and **non-corrosive parts**
- **Short worldwide delivery period** with tracking feature & insurance
- **2 years full warranty with extension option** for all DEKAL load banks
- CE certification - health, safety, and environmental protection standards
- Made for GPU's testing procedure according to ISO 6858, DFS 400, ARP 5015
- Classification CE marking, DIN, VDE, IEC, IP 21 protection rate level



NCAGE CODE: 1267Q



Excellent SME

